



NORLOG

www.norlog-group.co.uk

## INSTRUCTIONS: Giant Wishing Well.

**PLEASE READ BEFORE YOU START BUILD.**



Find a clean and level place to build your wishing well.

Start with 3 half logs they are all the same length note the direction of cut-outs. fig 1.

Continue the build with whole logs 3 per row (39 logs); make sure the cut outs are in line with each other before you tap together. (a rubber or wood hammer is the best tool to use). fig 2.

Place the seats on as main picture (do not fix yet) offer the uprights to the centre of the pool walls (between seats) screw each upright in place with 4 x 80mm screws provided. fig 8

Fix the 6 roof panels together fig 7 making the hexagon shape screw the finial in the hole at top of completed roof. (3 brackets per roof 25mm screws) offer the completed roof to the top of the uprights fixing them to the centre of the middle roof brace 60mm screws. fig 5

**MAKE SURE THERE ARE NO SHARP OBJECTS UNDER THE LINER AS THIS WILL CAUSE A PUNCTURE** remove the seats and place the liner inside the pool base matching the liner shape to the frame shape. **We recommend you have 20mm of soft sand under the liner.** Hook the liner hoops over the top 2 logs. fig 3.

Fill with water and fix the 3 batons in place with pins. fig 6 (**ONLY DO THIS WHEN THE POOL IS FULL.**)

Place the seats on and screw in place 80mm screws. (top log to top log). fig 4

fig1



fig2




fig3



fig4

fig5


fig6



fig7



fig8



Norlog. Unit 9N Site A Rednal Industrial Estate Rednal Oswestry Shropshire SY11 4HS  
Tel/Fax: 01691 610000. Email: [info@norlog-group.co.uk](mailto:info@norlog-group.co.uk)  
[www.norlog-group.co.uk](http://www.norlog-group.co.uk)